

$\chi_{3NO+1NC}$

K

■ 1002



ᠠ ᠨ ᠳ ᠢ ᠶ	24V AC/DC
ᠳ ᠢ ᠬ ᠲ	0.85 ~ 1.1
ᠦ ᠯ ᠤ ᠶ	50Hz ~ 60Hz
ᠹ ᠢ ᠠ	≤ 2.2W/24V DC, ≤ 5.4VA/24V AC
ᠵ ᠢ ᠳ ᠯ	≤ 50mA/24V DC
ᠮ ᠠ ᠳ ᠬ	≤ 15Ω
ᠵ ᠢ ᠳ ᠬ	
ᠮ ᠠ ᠳ ᠬ	2 ~ 20kΩ
ᠤ ᠶ ᠹ	3NO+1NC
ᠤ ᠶ ᠠ ᠵ	
ᠤ ᠶ ᠠ	AgSnO ₂ +0.2μmAu
ᠤ ᠶ ᠬ	AC-15: 5A/230V, DC-13: 5A/24V
ᠤ ᠶ ᠶ ᠠ ᠵ ᠢ	10A gL/gG(NO), 6A gL/gG(NC)
ᠲ ᠨ ᠵ	≤ 100ms
ᠶ ᠹ ᠨ ᠵ	: ≤ 30ms, : ≤ 100ms
ᠹ ᠮ ᠨ ᠵ	: ≤ 30ms, : ≤ 100ms
ᠳ ᠠ ᠨ ᠨ ᠠ ᠠ	20ms
ᠳ ᠡ ᠯ ᠬ	IEC/EN 60947, IEC 61326-3-1, IEC/EN 61000-6-2, IEC/EN 61000-6-4
ᠠ ᠨ ᠨ ᠠ ᠳ ᠢ ᠶ	250V AC
ᠠ ᠨ ᠨ ᠨ ᠠ ᠶ ᠳ ᠢ ᠶ	6000V(1.2/50us)
ᠨ ᠠ ᠠ ᠶ	1500V AC, 1 min
ᠳ ᠠ ᠵ ᠵ ᠵ ᠵ ᠵ ᠵ ᠵ ᠵ	IEC 60947-1
ᠤ	10Hz ~ 55Hz, 0.35mm
ᠶ ᠶ ᠶ ᠠ	III
/ ... ᠶ ᠠ	2
ᠵ ᠢ ᠶ ᠠ	IP20
ᠲ ᠠ ᠶ ᠶ	-20°C ~ +60°C
ᠴ ᠡ ᠶ ᠶ	-40°C ~ +80°C
ᠲ ᠠ ᠶ ᠶ	≤ 2000 m
ᠠ ᠨ ᠤ	10×10 ⁶ cycles

ó ħ ı ı	PLd, ISO 13849
Ĝ ı ı	Cat.3, ISO 13849
γ n ħ ħ	20, ISO 13849
W z ... Ā ħ ~ '	99%, ISO 13849
W z n ħ, ǫ ħ ħ	162, ISO 13849
H ħ, ǫ	68, ISO 13849
Ĝ ı ħ ħ ǫ ı ı	SIL2, IEC 61508
φ " Ĝ ı ħ ħ ǫ ı ı	SIL CL2, IEC 62061
. ħ ǫ ǫ ħ	1, IEC 62061
Ĝ ı, ǫ, "ǫ	≥ 99%, IEC 62061
ı ǫ ħ n ħ, ǫ ħ '	1.65×10 ⁻⁵ /PTI=20年, IEC 61508
¼ n ħ n ħ, ǫ ħ '	1.91×10 ⁻¹⁰ 1/h, IEC 62061
ȳ ħ ı	0, IEC 60204